

2010 MODEL SPECIFICATIONS

	BULLDOG	COYOTE	K-9 / K-9 EFI	MASTIFF / MASTIFF EFI	PITBULL	RIDGEBACK	WOLF
Dry Weight Front	322 lbs (146 kg)	261 lbs (118 kg)	263 lbs (119 kg)	280 lbs (127 kg)	295 lbs (134 kg)	259 lbs (116 kg)	305 lbs (138 kg)
Dry Weight Rear	446 lbs (202 kg)	404 lbs (183 kg)	442 lbs (200 kg)	424 lbs (192 kg)	396 lbs (179 kg)	421 lbs (191 kg)	465 lbs (211 kg)
Dry Weight Total	768 lbs (348 kg)	662 lbs (300 kg)	705 lbs (320 kg)	704 lbs (319 kg)	691 lbs (313 kg)	680 lbs (308 kg)	770 lbs (349 kg)
GVWR	1208 lbs (548 kg)	1012 lbs (459 kg)	1130 lbs (512 kg)	1130 lbs (512 kg)	1085 lbs (492 kg)	1085 lbs (492 kg)	1195 lbs (542 kg)
GAWR Front	424 lbs (192 kg)	345 lbs (156 kg)	390 lbs (177 kg)	390 lbs (177 kg)	360 lbs (163 kg)	390 lbs (177 kg)	407 lbs (185 kg)
GAWR Rear	783 lbs (355 kg)	667 lbs (303 kg)	740 lbs (336 kg)	740 lbs (336 kg)	725 lbs (328 kg)	695 lbs (315 kg)	787 lbs (357 kg)
Fuel - Total	4.5 gal (17 L)	3.8 gal (14.4 L)	4.4 gal (16.6 L) / 4.1 gal (15.5 L)	4.6 gal (17.4 L)	4.7 gal (17.8 L)	4.4 gal (16.6 L)	4.5 gal (17 L)
Fuel - Main	4.1 gal (15.5 L)	3.4 gal (13 L)	4.0 gal (15.1 L) / 3.7 gal (14 L)	3.9 gal (14.7 L) / 3.0 gal (11 L)	3.9 gal (14.7 L)	4.0 gal (15.1 L)	4.1 gal (15.5 L)
Fuel - Reserve	0.4 gal (1.5 L)	0.4 gal (1.5 L)	0.4 (1.5 L)	0.7 gal (2.7 L) / 1.6 gal (6 L)	0.8 gal (3.02 L)	0.4 gal (1.5 L)	0.4 gal (1.5 L)
Oil Capacity	3.5 qts (3.3 L)	3 qts (2.8 L)	3 qts (2.8 L)	3 qts (2.8 L)	3.75 qts (3.5 L)	3 qts (2.8 L)	3.3 qts (3.1 L)
Frame Rake	34 degrees	39 degrees	39 degrees	39 degrees	33 degrees	39 degrees	40 degrees
Tree Rake	3 degrees	3 degrees	3 degrees	3 degrees	0 degrees	3 degrees	5 degrees
Trail	4.8" (121.9 mm)	4.74" (120.3 mm)	4.68" (118.8 mm)	4.81" (122.2 mm)	5.59" (142 mm)	4.68" (118.8 mm)	5.86" (148.8 mm)
Front Suspension	41 mm Telescopic	41 mm Telescopic	41 mm Telescopic	41 mm Telescopic	41 mm Telescopic	41 mm Telescopic	41 mm Telescopic Sleeved
Fork Length	-1" (-25.4 mm)	+2.0" (50.8 mm)	+12.0" (304.8 mm)	+2.0" (50.8 mm)	-1.0" (-25.4 mm)	+12.0" (304.8 mm)	+3.0" (76.2 mm)
Seat Height	24.25" (616 mm)	24.5" (622.3 mm)	24.25" (616 mm)	24.25" (616 mm)	25.5" (647.7 mm) Spring Seat	24.25" (616 mm)	25.5" (647.7 mm)
Ground Clearance	4.5" (114.3 mm)	4.5" (114.3 mm)	4.0" (101.6 mm)	4.0" (101.6 mm)	4.75" (120 mm)	4.5" (114.3 mm)	3.875" (98.4 mm)
Wheel Base	74.63" (1895.6 mm)	77.5" (1969 mm)	82" (2083 mm)	77.5" (1968 mm)	73" (1857 mm)	82.5" (2096 mm)	83.5" (2120.9 mm)
Total Length	101.5" (2578 mm)	102.5" (2604 mm)	108" (2743 mm)	103" (2616 mm)	101.8" (2586 mm)	107" (2718 mm)	112" (2844.8mm)
Front Brake	4-Piston Diff Bore	4-Piston Diff Bore	4-Piston Diff Bore	4-Piston Diff Bore	4-Piston Diff Bore	4-Piston Diff Bore	4-Piston Diff Bore
Rear Brake	4-Piston	4-Piston	4-Piston	4-Piston	4-Piston	4-Piston	4-Piston Drive side
Front Tire	120/70 R21 62V	MH90-21 56V	MH90-21 56V	MH120/70-21 62V	130/60 R23 65V	MH90-21 56H	130/60R23 65V
Rear Tire	250/40 R18 81V	250/40 R18 81V	300/35 R18 87V	300/35 R18 87V	280/40 R20 89V	330/30 R17 87V	220/50R20 83V
Tire Pressure	F:40 psi (275.8 kPa) R: 42 psi (289.5 kPa)	F:40 psi (275.8 kPa) R: 42 psi (289.5 kPa)	F:40 psi (275.8 kPa) R: 42 psi (289.5 kPa)	F:40 psi (275.8 kPa) R: 42 psi (289.5 kPa)	F:40 psi (275.8 kPa) R: 42 psi (289.5 kPa)	F:40 psi (275.8 kPa) R: 42 psi (289.5 kPa)	F:40 psi (275.8 kPa) R: 42 psi (289.5 kPa)
Front Wheel	21" x 3.25" (533.4 mm x 82.5 mm)	21" x 2.15" (533.4 mm x 54.6 mm)	21" x 2.15" (533.4 mm x 54.6 mm)	21" x 3.25" (533.4 mm x 82.5 mm)	23" x 3.75" (584.2 mm x 95.25 mm)	21" x 2.15" (533.4 mm x 54.6 mm)	23" x 3.75" (584.2 mm x 95.25 mm)
Rear Wheel	18" x 8.50" (457.2 mm x 215.9 mm)	18" x 8.50" (457.2 mm x 215.9 mm)	18" x 10.50" (457.2 mm x 266.7 mm)	18" x 10.50" (457.2 mm x 266.7 mm)	20" x 10.50" (508.0 mm x 266.7 mm)	17" x 12.00" (431.8 mm x 304.8 mm)	20" x 7.00" (508.0 mm x 177.8 mm)
Engine	OHV 45 degree V-Twin	OHV 45 degree V-Twin	OHV 45 degree V-Twin	OHV 45 degree V-Twin	OHV 45 degree V-Twin	OHV 45 degree V-Twin	OHV 56 degree X-Wedge
Displacement	111 c.i. (1807 cc)	117 c.i. (1917 cc)	117 c.i. (1917 cc)	117 c.i. (1917 cc)	117 c.i. (1917 cc)	117 c.i. (1917 cc)	121 c.i. (1976 cc)
Bore x Stroke	4.125" x 4.125" (104.8 mm x 104.8 mm)	4.125" x 4.375" (104.8 mm x 111.1 mm)	4.125" x 4.375" (104.8 mm x 111.1 mm)	4.125" x 4.375" (104.8 mm x 111.1 mm)	4.125" x 4.375" (104.8 mm x 111.1 mm)	4.125" x 4.375" (104.8 mm x 111.1 mm)	4.25" x 4.25" (107.95 mm x 107.95 mm)
Compression Ratio	9.7:1	9.6:1	9.6:1	9.6:1	9.6:1	9.6:1	9.9:1
Fuel System	CLEFI	Carbureted	Carbureted / CLEFI	Carbureted / CLEFI	Carbureted	Carbureted	CLEFI
Transmission	6-Speed	6-Speed	6-Speed	6-Speed	6-Speed	6-Speed	6-Speed
Primary Drive	Comp/Balance Drive	Comp/Balance Drive	Comp/Balance Drive	Comp/Balance Drive	Comp/Balance Drive	Comp/Balance Drive	Comp/Balance Drive
Final Drive	1.125" (28.6 mm) Belt	1.125" (28.6 mm) Belt	1.125" (28.6 mm) Belt	1.125" (28.6 mm) Belt	1.125" (28.6 mm) Belt	1.125" (28.6 mm) Belt	1.125" (28.6 mm) Belt

All models: **Ignition** - Electronic Single Fire; **Charging Output** - 35 Amp; **Battery** - 310 CCA/Sealed AGM

BULLDOG SADDLEBAGS: Cargo Weight Capacity - 15lbs (6.8 kg) per side, maximum; **Internal Volume** - Right Hand 0.968 cu. ft. (0.027 cu m), Left Hand 1.01 cu. ft. (0.029 cu m)

